



Class 150 & Class 300 Triple Offset Flange Butterfly Valve

Class	Size		Dimensions (mm)				Weight (Kg)	
	NPS	DN	L	H ₁	H ₂	D		
150	2	50	108	305	115	160	21	
	2 1/2	65	112	315	125	160	24	
	3	80	114	330	135	160	27	
	4	100	127	360	140	160	28	
	5	125	140	140	450	170	280	30
	6	150	150	140	475	175	280	50
	8	200	152	152	525	240	280	75
	10	250	165	165	570	270	280	105
	12	300	178	178	630	315	320	155
	14	350	190	190	675	345	350	190
	16	400	216	216	720	395	350	230
	18	450	222	222	805	405	350	300
	20	500	229	229	895	430	400	380
	24	600	267	267	950	500	400	490
	26	650	267	267	960	515	400	580
	28	700	292	292	1030	520	400	660
	30	750	308	308	1080	545	450	740
	32	800	318	318	1135	620	450	820
36	900	330	330	1175	620	450	1100	
40	1000	410	410	1270	720	500	1430	
44	1100	450	450	1335	768	500	2200	
300	2	50	150	315	115	500	32	
	2 1/2	65	170	325	125	160	39	
	3	80	180	340	135	160	42	
	4	100	190	435	140	160	45	
	5	125	200	475	170	280	48	
	6	150	210	510	220	280	80	
	8	200	230	520	240	280	120	
	10	250	250	625	270	280	168	
	12	300	270	670	320	350	248	
	14	350	290	765	370	350	304	
	16	400	310	840	410	350	368	
	18	450	330	910	420	400	480	
	20	500	350	980	460	400	608	
	24	600	390	1080	540	400	784	
	26	650	390	1130	585	450	928	
	28	700	430	1175	640	450	1056	
	30	750	430	1265	700	500	1184	
	32	800	470	1300	765	500	1312	
36	900	510	1380	820	500	1760		
40	1000	550	1460	890	500	2288		

Noted: We may provide other different actuators according to the customer's request, such as pneumatic, electric, hydraulic actuators, the details of them according to the actual valve working condition.