

GLOBE VALVE 150Lb

GLOB VALF 150Lb

VBV-C150



Globe Valves

Class 150

ANSI B16,10

ANSI B16,5/Flange

- Flanged(FLGD)

- Bolted Bonnet(BB)

- Rising stem and handwheel(RS)

- Outside screw and yoke(OSY)

Bolted Gland (BG)

Renewable seat(Optional)

NO	PART NAME	PARÇAAADI	MATERIAL / MALZEME
1	Body	Gövde	ASTM A126 / ASTM A536 / ASTM A216 WCB
2	Body Seat	Gövde Siti	Rg-5 Bronze (ASTM B62) / SS304 / SS316
3	Disc	Disk	Rg-5 Bronze (ASTM B62) / SS304 / SS316
4	Disc Nut	Disk Somunu	Brass / SS304) / SS316
5	Stem	Mil	CuZn35Ni / SS420 / SS304 / SS316
6	Gasket	Conta	Klingerite / Graphite
7	Bonnet	Kapak	ASTM A126 / ASTM A536 / ASTM A216 WCB
8	Back Seat	Geri Sit	Brass / SS420 / SS304 / SS316
9	Packing	Salmastra	Graphite
10	Pcking Nut	Salmastra Baskısı	ASTM A395 / ASTM A126 / WCB
11	Gland Flange	Salmastra Baskısı Flaşı	ASTM A395 / ASTM A126 / WCB
12	Stem Bushing	Mil Yatağı(Opsiyonel)	ASTM A126 / ASTM A536 / ASTM A216 WCB
13	Stud	Saplama	Steel / SS A2 / SS A4
14	Nut	Somun	Steel / SS A2 / SS A4
15	Handwheel	Volan	Ductile Iron
16	Handwheel Nut	Volan Somunu	Steel



DN		Valve Dimensions Vana Boyutları ANSI B16,10			Flange Dimensions Flaş Ölçüleri ANSI B16,5					Diameter Ağırlık kg
mm	Inch	L	H	ØM	ØD	Øk	Øg	b	ØIxn	
15	1/2"	108	185		89	60,5	35	10		4
20	3/4"	117	205	100	99	70	43	10,5		4,5
25	1"	127	210		108	79,2	51	11,5	Ø16x4	5,5
32	1 1/4"	140	220		117	89	64	13		9
40	1 1/2"	165	240	140	127	98,6	73	14,5		12
50	2"	203	330		152,5	120,7	92	16		17
65	2 1/2"	216	360	200	178	139,7	105	17,5	Ø19x4	23
80	3"	241	382	250	190,5	152,4	127	19		37
100	4"	292	445		229	190,5	157	24	Ø19x8	47
125	5"	355,6	485	355	254	216	185,7	24		71
150	6"	406,4	540		279,5	241,3	216	25,5		86
200	8"	495	620		343	298,5	270	28,5	Ø22x8	130
250	10"	622	770	450	406,5	362	324	30,2		205
300	12"	698,5	880	550	483	431,8	381	32	Ø22,5x12	325
350	14"	787	1100		533	476	413	35	Ø29x12	
400	16"	914	1250	650	597	539,5	470	36,6	Ø29x16	

